

SAFETY DATA SHEET

1. Identification

Product Identifier: PolyCoat
Product Code(s): POLYCOAT

Use: Semi-Permanent Sealer and Release Agent

For Industrial/Professional use only.

Manufacturer: Polytek Development Corp.

55 Hilton St., Easton, PA 18042

Phone Number: 610-559-8620 (9 a.m. to 5 p.m. EST) Emergency Phone: CHEMTREC 800-424-9300 or

+1 (703) 527-3887

E-mail: sds@polytek.com

2. Hazards Identification

GHS Classification:

Flammable Liquid Category 2 Skin Irritation Category 2

Specific Target Organ Toxicity (Single Exposure) Category 3

Aspiration Hazard Category 1

Hazardous to the Aquatic Environment - Chronic Category 2

Label Elements: Danger









Hazard Phrases

H225 Highly flammable Liquid and vapor

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

Precautionary Phrases

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat, sparks, open flames and hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/Bond container and receiving equipment.

P242 Use only non-sparking tools.

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection.

P301 + 310 IF SWALLOWED: Immediately call a poison center or

doctor.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P308+313 IF exposed or concerned: Get medical attention.

P331 Do NOT induce vomiting.

P403+235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents and container to licensed, permitted

incinerator, or other thermal destruction device in accordance with local and national regulations.

3. Composition/Information on Ingredients

Chemical Name	CAS#	%
Aliphatic Hydrocarbon	90622-56-3	80-95

4. First-Aid Measures

Eye Contact: Rinse thoroughly with water for at least 15 minutes, holding the eyelids open to be sure the material is washed out. Get prompt medical attention.

Skin Contact: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop.

Inhalation: Remove person to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Do not induce vomiting. Get medical attention. **Most Important Symptoms/Effects:** Not data available.

Indication of Immediate Medical Attention/Special Treatment: No data available.

5. Fire-Fighting Measures

Extinguishing Media: Use foam, dry chemical or carbon dioxide.

Specific Hazards: None known.

Special Protective Equipment & Precautions for Fire-Fighters: Wear positive pressure, self-contained breathing apparatus and full-body protective clothing.

6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency

Procedures: Remove all ignition sources. Use non-sparking tools. Wear gloves and safety glasses.

Methods and Materials for Containment and Cleanup: Cover with an inert absorbent material and collect into an appropriate container for disposal.

7. Handling and Storage

Safe Handling: Keep away from heat, sparks, open flames and hot surfaces. No smoking. Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area.

Safe Storage: Store in a cool, dry area. Store in original containers. Keep container closed when not in use.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits: No known exposure limits are established by regulatory authorities. Manufacturer recommends exposure limit of 300 ppm, 8-hr TWA.

Ventilation: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Respiratory Protection: If needed, an approved respirator with organic vapor cartridges may be used. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

Skin Protection: Wear impervious gloves, such as butyl rubber or nitrile rubber.

Eye Protection: Wear safety glasses or goggles.

Other Protective Measures: An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and Chemical Properties

Appearance: Clear liquid

Odor: Paraffinic

Odor Threshold: No data available

pH: Not applicable

Melting Point: No data available

Date Prepared/Revised: Feb. 4, 2014; Supersedes: Jan. 7, 2014 Z:\MSDS\RELEASES\PolyCoat-14.docx



SAFETY DATA SHEET

Boiling Point: 240-280°F/116-138°C **Flash Point:** <23°C (73°F) (C.O.C.) **Evap. Rate:** >1 (butyl acetate=1) **Flammability Limits:** No data available

Vapor Pressure: 63 mm Hg @ 68°F (estimated)

Vapor Density: >1 (air=1) **Relative Density:** 0.73 @ 25°C **Solubility:** Insoluble in water

Partition Coefficient: No data available Auto-Ignition Temp: No data available Decomposition Temp: No data available

Viscosity: <15 cps @ 25°C % Volatile by Volume: 96

10. Stability and Reactivity

Reactivity: Not normally reactive.

Chemical Stability: Stable under recommended conditions.

Possibility of Hazardous Reactions Under recommended conditions of

storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid moisture and extreme temperatures to

protect product integrity.

Incompatible Materials: Avoid contact with water, strong acids,

oxidizers, and alkalis.

Hazardous Decomposition Products: Carbon monoxide, carbon

dioxide, nitrogen oxides, and formaldehyde.

11. Toxicological Information

Eye Contact: May cause eye irritation and/or tissue damage. **Skin Contact:** Causes skin irritation and possibly dermatitis. Can be absorbed through the skin and lead to central nervous system effects. **Inhalation:** May cause respiratory tract irritation, headaches, dizziness, drowsiness, anemia, nausea, and other central nervous system effects (e.g., loss of coordination, and fatigue).

Ingestion: May cause drowsiness, anemia, nausea, and other central

nervous system effects.

Chronic Health Effects: No data available. Acute Toxicity Values: No data available.

Germ Cell Mutagenicity: Components are not mutagens.

Carcinogenicity: To the best of our knowledge, this product does not contain constituents at concentrations exceeding 0.1% that are listed as carcinogens by IARC, NTP, or OSHA.

Reproductive Toxicity: Components are not reproductive toxins.

Specific Target Organ Toxicity:

Single Exposure: Causes central nervous system effects, such as headaches, dizziness, drowsiness, anemia, nausea, loss of coordination, and/or fatigue.

Repeat Exposure: No data available.

12. Ecological Information

Ecotoxicity: For CAS 90622-56-3, 96-hr LC50 is 124 mg/l (fathead minnow). No other specific data, but manufacturer designated product Aquatic Toxicity Chronic, Category 2.

Persistence and Degradability: No data available. Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. Disposal Considerations

Dispose according to local, state and federal regulations. For U.S.: Upon disposal, PolyCoat is a RCRA hazardous waste (D001: per 40 CFR 261).

14. Transport Information

UN Number: 1866

UN Proper Shipping Name: Resin Solution Transport Hazard Class: 3, Flammable Liquid

Packing Group: III

Environmental Hazards: Aquatic Toxicity – Chronic Cat. 2

Transport in Bulk: Not applicable **Special Precautions:** None known

Emergency Shipping Info: CHEMTREC, 800-424-9300 or +1-703-527-3887

15. Regulatory Information

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local and state regulations.

SARA TITLE III

Section 311/312: Acute Health

Section 313 Toxic Chemicals: This product contains no chemicals subject to SARA Title III Section 313 Reporting requirements. Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

STATE REGULATIONS:

California Proposition 65: To the best of our knowledge, this product does NOT contain substances known to the State of California to cause cancer and/or reproductive harm.

16. Other Information

Training Advice: All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

Recommended Uses and Restrictions: This product is intended for Industrial/Professional use only.

SDS Revision Notes: Converted to GHS format. Correction in Section 13.

Disclaimer: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.